


ELECTRICAL CHARACTERISTICS
 NOM. VOLTAGE RATING, kV 23
 DRY 60 HZ F.O., kV 80
 WET 60 HZ F.O., kV 60
 POS. CRITICAL IMPULSE F.O. kV 130
 NEG. CRITICAL IMPULSE F.O. kV 155
 RIV CHARACTERISTICS
 60 Hz TEST VOLTAGE, kV 15
 MAX. RIV AT 1000 KHZ, MV 100
 MECHANICAL CHARACTERISTICS
 CANTILEVER STRENGTH, LBS 2800
 CANTILEVER PROOF TEST (MIN.) LBS 1400
 PHYSICAL CHARACTERISTICS
 LEAKAGE DISTANCE, IN 14
 DRY ARCING DISTANCE, IN 6.5
 PORCELAIN DIAMETER, IN 6.5
 COLOR: GRAY
 TESTED PER ANSI C29.1 & ANSI C 29.7



A
 M3:1

					57-11		DRAWING #				
					INSULATOR		PHASE	SIGN	WEIGHT	SCALE	
							TOTAL 2 PAGES		PAGE 1		
					INSULATOR		NEWELL- PSN LLC				
SIGN	QTY	REJIGGER #	NAME	DATE							
DRAWN											
CHECKED											
APPROVE											
DATE											