


MECHANICAL CHARACTERISTICS	
CANTILEVER STRENGTH, LBS	8000
TENSILE STRENGTH, LBS	28000
TORSIONAL STRENGTH, IN-LBS	40000
COMPRESSION STRENGTH, LBS	40000
ELECTRICAL CHARACTERISTICS	
POS. CRITICAL F. O., kV	125
IMPULSE WITHSTAND, kV	110
60 HZ WET WITHSTAND, kV	45
RIV CHARACTERISTICS	
60 HZ TEST VOLTAGE, kV	10
MAX. RIV AT 1000 KHz, vV	50
PHYSICAL CHARACTERISTICS	
LEAKAGE DISTANCE, IN	15.5
COLOR: GRAY	
TESTED PER ANSI C29.1 (LATEST REVISION) & ANSI C 29.9 (LATEST REVISION)	

5/8" - 11UFS-2B
4 HOLES AT 90° ON 5.00" B.C.,
5/8" DEEP BOTH ENDS



AB

				110kV -BIL NON-STACKING STATION POST		DRAWING #	041012	
						PHASE SIGN	WEIGHT	SCALE
						TOTAL 1 PAGES		PAGE 1
SIGN	QTY	RE JIGGER #	NAME	DATE	INSULATOR		NEWELL-PSN LLC	
DRAWN								
CHECKED								
APPROVE								
DATE					MATERIAL	PORCELAIN		