


MECHANICAL CHARACTERISTICS	
CANTILEVER STRENGTH, LBS	8000
TENSILE STRENGTH, LBS	28000
TORSIONAL STRENGTH, IN-LBS	40000
COMPRESSION STRENGTH, LBS	40000
ELECTRICAL CHARACTERISTICS	
POS. CRITICAL F. O., kV	225
IMPULSE WITHSTAND, kV	200
60 HZ WET WITHSTAND, kV	80
RIV CHARACTERISTICS	
60 HZ TEST VOLTAGE, kV	22
MAX. RIV AT 1000 KHz, vV	100
PHYSICAL CHARACTERISTICS	
LEAKAGE DISTANCE, IN	37
COLOR: GRAY	
TESTED PER ANSI C29.1 (LATEST REVISION) & ANSI C 29.9 (LATEST REVISION)	

5/16" - 11UFS-2B  
4 HOLES AT 90° ON 5.00" B.C.,  
3/4" DEEP BOTH ENDS



AB

					200kV -BIL NON-STACKING STATION POST		DRAWING #	041020	
							PHASE SIGN	WEIGHT	SCALE
							TOTAL 1 PAGES		PAGE 1
					INSULATOR		NEWELL-PSN LLC		
SIGN	QTY	REJIGGER #	NAME	DATE	MATERIAL	PORCELAIN			
DRAWN									
CHECKED									
APPROVE									
DATE									