


RELEASE HISTORY

a	DRAWING/DESIGN CREATED Rev.0	26.02.2016 SNR
b	DRAWING REDRAWN Rev.1	26.03.2021 RVS



PART# 41515-7001

DRAWING NUMBER NP1577

TITLE STATION POST INSULATOR-150kV BIL

REF. TECHNICAL REFERENCE TR-227

TECHNICAL CHARACTERISTICS**MECHANICAL RATINGS**

CANTILEVER STRENGTH, lbs (kN) (Upright & Underhung)	4000 (17.8)
TENSION STRENGTH, lbs (kN)	20000 (89)
TORSION STRENGTH in-lbs (kN*M)	16000 (1.8)
COMPRESSION STRENGTH lbs (kN)	20000 (89)

ELECTRICAL RATINGS

IMPULSE WITHSTAND VOLTAGE, kV	150
CRITICAL IMPULSE FLASHOVER VOLTAGE, POSITIVE, kV	170
WET POWER FREQUENCY WITHSTAND VOLTAGE, kV	60


RADIO INFLUENCE VOLTAGE RATINGS

LOW FREQUENCY TEST VOLTAGE, kV	15
MAX. RIV AT 1000 kHz, μ V	100

PHYSICAL CHARACTERISTICS

MINIMUM LEAKAGE DISTANCE, in (mm)	24 (610)
UNIT HEIGHT, in (mm)	15 (381)
NET WEIGHT, lbs (kg)	43 (19.5)
GLAZE COLOR	Light Gray

APPLICABLE STANDARD:ANSI:C29.9 & C29.1



4 Holes 5/8"-11UNC(0.015" Oversize)
X 20mm deep on 5" PCD

5	FITTING	1	
4	PORCELAIN	1	
3	CEMENT		
2	CORK	1	
1	FITTING	1	
S.No.	DESCRIPTION	QUANTITY	REMARKS

REF.

DWG.TYPE SALES

DWN. RVS

APP.